

The DEAD-STOP-2 is a 2" overfill prevention valve with a ZERO leak rate, suitable for commercial above ground diesel storage installations, generator belly tanks and pressure deliveries.

With a flow rate of 10 – 500 l/min and a maximum operating pressure of 10 bar (145 psi) the DEAD-STOP-2 is suitable for a range of applications, protecting against the risk of an overfill should other methods fail.



### A high-quality overfill prevention valve with Zero leak rate.

Suitable for commercial above ground storage tank installation and pressure deliveries, incorporating many proven features from our RIS-STOP range. Includes a 2" PCAT flanged inlet on the body allowing easy pipework connection and alignment.

- Cartridge construction for easy installation and in-situ examination via a single 2" aperture.
- High flow capacity
- Effective at low flow rates (10 – 500 l/m) pressure delivery up to 10 bar maximum.
- Suitable for fuels of SAE10 or lower
- Compatible with all pipework brands
- Flexible connectors are available, to make installation easy and remove stress from pipework, which can distort the valve and prevent it from operating correctly
- The valve shuts in the direction of the flow, ensuring a positive seal maintained by the fill pressure
- 100% tested in factory

#### Materials:

Anodised Aluminium  
Viton A (FKM)  
Stainless Steel  
HDPE closed cell foam

#### Suitable for:

Diesel  
Bio-Diesel  
FAME Blends

#### Document Ref:

DATA-DEAD-STOP-2-230216

#### Installation Instructions

INS-DEAD-STOP-2-~

#### Maintenance Instructions

MAINT-DEAD-STOP-2-~