

Pt No. RIS-PRESSURE-DIP-KEY (red key only)



Pt No. RIS-PRESSURE-DIPXI

Assembled with a dip-rod (shown)  
(dip-rod not supplied by Risbridger) and  
special tamper proof key (shown)



Pt No. RIS-PRESSURE-DIP-FA  
shown with upper and lower  
dip tubes (not supplied by  
Risbridger)



### Available configurations:

#### 2" RIS-FLANGE:

Swivel base to allow easy alignment - fits to 2"  
flange port on RIS-FLANGE lids (or to 4" port  
with use of 4 to 2 Adaptor plate)

#### THREADED VERSION:

RIS-FLANGE thread base adaptor

Part of the RIS-FLANGE Tanklid System, or configured for standard threaded tank lids, this item is designed to allow dip testing for water contamination of tanks on Stage II Vapour Recovery sites. It is specifically designed to prevent release of high volumes of vapour to the atmosphere, by means of a liquid sealed dipping tube.

- Two level position prevents the dip rod from resting on tank floor when not in use
- Secure locking key prevents un-authorised use or access to the dip cap assembly
- Suitable for use with Bio-Fuel Blends up to 90%
- Can be fitted to any RIS-FLANGE tank lids or standard threaded lids
- Dip rod drilling jig available for installation contractors

#### Materials:

Anodised Aluminium  
Viton A (FKM)  
Stainless Steel

#### Suitable for:

Petroleum Spirit (including  
Ethanol Blends up to 90%)  
Diesel  
Bio Diesel / FAME Blends

#### Document Ref:

DATA-RIS-PRESSURE-DIP-150909  
**Maintenance Instructions**  
MAINT-RIS-PRESSURE-DIP  
**Installation Instructions**  
INS-PRESSURE-DIP