

TECOIL®

Oil Reeling Hose

TECOIL® domestic oil reeling hose uses a revolutionary specially formulated cover that drastically reduces drag coefficient resulting in a hose that is much easier to pull, is longer lasting and has much less wear on tear on reeling equipment.

Used day-in, day-out, **TECOIL®** has demonstrated flow rates of up to 375 liters/min*.

**(Kerosene-pump equipment dependent)*



Superior Drag Performance

- Reduced drag co-efficient makes for easy operator handling, minimizing the risk of a manual handling injury.
- Highly wear resistant cover, maximizes service life & total cost of ownership.
- One year warranty.
- Dilation and elongation - exceed Trading standard requirements, under operating pressure and flow conditions. Independent results available on request.

Technical Information

Application	Heavy Duty oil reeling applications
Tube	Black conductive NBR
Reinforcement	High Tensile 2 Polyester braids
Cover	Red SBR/NVC cover - highly abrasion, ozone and hydrocarbon resistant
Working Temp	-20°C to +80°C
Features	61m (200ft) Colour red
Working Pressure	16 bar
Safety Factor	3:1
Standard	ISO EN1360:2005

Inner Diameter	35mm
Outer Diameter	48mm
Weight	1.143kg per meter
Min Bend Radius	210mm

TEC Industrial

www.tecindustrial.ie | +353 1 457 3533

Email: sales@tecindustrial.ie | Fax: (01) 457 3627

Unit C3 Weatherwell Business Park, Ninth Lock Road,
Clondalkin, Dublin, D22 P803, Ireland.

