

Braided flexible connectors for pressure fill applications.

Pt No. 5574 (3" ANSI 150 TO 3" PCAT)
Approximately 320mm long



Pt No. 5575 (3" ANSI 300 TO 3" PCAT)
Approximately 320mm long



Pt No. 5576 (4" PCAT TO 3" PCAT)
Approximately 305mm long



Pt No. 5577 (3" PCAT TO 3" PCAT)
Approximately 305mm long



Materials:

Zinc plated mild steel Stainless steel

Suitable for:

Petroleum Spirit (including Ethanol Blends up to 90%) Diesel Bio Diesel / FAME Blends AvGas and Jetfuel

Document Ref:

DATA-FLEXI



Standard flexible connectors for gravity fill applications

Pt No. AH5090FL-FL (2" PCAT TO 2" PCAT)
Approximately 90mm long



Pt No. AH50160FL-FL (2" PCAT TO 2" PCAT)
Approximately 160mm long



Pt No. AH100200FL-FL (4" PCAT TO 4" PCAT)
Approximately 200mm long



Pt No. 5295(3" PCAT TO 3" PCAT)
Approximately 150mm long



Materials:

Zinc plated mild steel Stainless steel

Suitable for:

Petroleum Spirit (including Ethanol Blends up to 90%) Diesel Bio Diesel / FAME Blends AvGas and Jetfuel

Document Ref:

DATA-FLEXI



Standard flexible connectors for gravity fill applications

Pt No. 5199 (3" ANSI 150 TO 3" PCAT)
Approximately 150mm long



Pt No. 5200 (3" ANSI 300 TO 3" PCAT)
Approximately 150mm long



Pt No. 5844 (4" PCAT TO 3" PCAT)
Approximately 90mm long



Pt No. 5047 (4" PCAT TO 3" PCAT)
Approximately 150mm long



Materials:

Zinc plated mild steel Stainless steel

Suitable for:

Petroleum Spirit (including Ethanol Blends up to 90%) Diesel Bio Diesel / FAME Blends AvGas and Jetfuel

Document Ref:

DATA-FLEXI